

RR KABEL FR HSF / FR-LSH / LSOH-FR

RR KABEL

Single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC/ Thermoplastic Halogen free Flame Retardant (HFFR) 70° Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code : 8544)

RATE / 100 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR HSF FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH-FR Thermoplastic Halogen Free Flame Retardant (HFFR) 70° C Insulation As Per IS 17048
10.0	140/0.3	52	22082	22852	24261
16.0	126/0.4	70	34953	36173	38208
25.0	196/0.4	88	56449	58708	63227
35.0	276/0.4	112	78964	82122	88438
50.0	396/0.4	146	112611	117112	126121
70.0	360/0.5	216	159587	165971	178736
95.0	480/0.5	262	214681	223268	240442
120.0	608/0.5	310	277780	288895	311117
150.0	750/0.5	355	344344	358122	385665
185.0	931/0.5	415	418789	435542	469041
240.0	1200/0.5	500	550952	572990	617067
300.0	1500/0.5	550	687810	715325	770347
400.0 *	2013/0.5	590	934641	972027	1046797
500.0 *	2562/0.5	660	1211516	1259974	1356896
630.0 *	3416/0.5	725	1610458	1674875	1803712

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

** RR Kabel LSOH-FR: Insulation conforming to HFI TP 70 as per IS 17048

RR KABEL FR HSF SINGLE CORE

RR KABEL

Multistrand bright electrolytic annealed bare copper conductor, FR PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts as per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	1266
0.75	24/0.2	8	1780
1.0	32/0.2	13	2319
1.5	30/0.25	17	3354
2.5	50/0.25	24	5463
4.0	56/0.3	30	8351
6.0	84/0.3	38	12425