

BRAIDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC Insulated, Annealed Tinned Copper Braided with Optimum coverage and Outer PVC sheathed Industrial Braided cables, Voltage Grade 300/500V.

Size in Sq.mm / Rate Per 100 Meter (in INR)						
SIZE	0.25	0.50	0.75	1.00	1.50	2.50
2 Core	8782	10114	10979	12426	15844	23193
3 Core	9448	11283	13637	15696	20482	30449
4 Core	11360	13800	16897	19872	25623	39053
5 Core	14228	16120	20227	23687	31311	48574
6 Core	16760	17799	21402	26871	35160	-
7 Core	17692	19323	24675	29657	39681	61729
8 Core	18956	21796	27624	33776	45839	-
9 Core	-	-	-	-	51283	-
10 Core	22649	27686	35099	41822	56974	-
12 Core	25098	30113	40260	48935	66362	103232
14 Core	-	34498	45947	56611	76989	-
16 Core	-	38832	51799	63719	86683	-
18 Core	35320	42854	58060	71278	96831	-

Size in Sq.mm / Rate Per 100 Meter (in INR)				
SIZE	4.0	6.0	10.0	16.0
2 Core	33482	46143	-	-
3 Core	45966	63934	-	-
4 Core	57868	81535	136880	221438

Note : Please contact HO for Technical Data Sheet.

Note : Minimum Order Quantity (MOQ)

Size - upto 0.25 x 8C - 5 KM, upto 0.25 x 8C to 18C and 0.50 to 1.50 x 7C - 3 KM,
0.50 x 8C to 4.0 x 4C - 2 KM, 0.50 x 22C to 1.00 x 27C - 2 KM.